

IN THE CLAIMS:

1. (Currently Amended) Communication device with casing parts enclosing a microphone and a receiver and suspension points therefore in the casing, ~~whereby further~~ including a sound canal from the receiver to the ear of a user ~~is provided~~, and wherein at least one of the casing parts are shaped from an injection moulded fibre-reinforced polymer which has a fibre ~~contents~~ content between 30% and 75% by weight.

2. (Currently Amended) Communication device as claimed in claim 1, whereby the fibre content is between 40% and 60% ~~and preferably at 50% by weight.~~

3. (Currently Amended) Communication device as claimed in ~~any of the above claims~~ claim 1, whereby the reinforced polymer is 'a polymylamide-based ~~or~~ compound and ~~where~~ the fibre-reinforcement comprises glass fibres.

4. (Currently Amended) Communication device as claimed in claim 1, ~~whereby~~ wherein the reinforced polymer is a polyamide-based compound.

5. (Currently Amended) Communication device as claimed in claim 1, ~~whereby~~ wherein the reinforced polymer compound has an B-module which is higher than 13 MPa.

6. (Currently Amended) Communication device as claimed in claim 1, ~~whereby~~ wherein the reinforced polymer compound has an B-module which is higher than 15 MPa.

7. (Currently Amended) Communication device as claimed in claim 1, ~~whereby~~ wherein the reinforced polymer compound has an B-module which is higher than 18 Mpa.

8. (Currently Amended) Communication device as claimed in ~~any of the above claims, whereby~~ claim 1, including a receiver enclosure is ~~provided~~ which has wall parts forming part of the casing which in cooperation with detachable wall parts form the enclosure in an air tight manner for sound isolation of the receiver.

9. (Currently Amended) Communication device as claimed in claim 8, ~~whereby~~ wherein at least ~~the~~ shell and wall parts forming the receiver enclosure are shaped from an injection moulded fibre-reinforced polymer.

10. (Currently Amended) Communication device as claimed in ~~any of the above claims, wherein~~ claim 1, wherein the casing comprises a first and a second part which are tightly joined along respective edge lines whereby a flexible packing or gasket material is provided in the edge line between the two casing parts.